Safety Data Sheet (SDS)

Revision Number: 4.0	Last updated 25 July 2019
1. Product and Company Identification	<u>on</u>
Product Name:	SHLP1 (Small humanin-like peptide 1) H-MCH WAG GAS NTG DAR GDV FGK QAG-OH
Manufacturer/Supplier:	AnaSpec, Inc. www.anaspec.com 34801 Campus Drive Fremont, CA 94555 Tel: 510-791-9560 Fax: 510-791-9572 Email: service@anaspec.com Kaneka Eurogentec SA, Rue du Bois Saint Jean 5 4102 Seraing Belgium Tel. +32-4-3727400 Fax. +32-4-3727500 E-mail info@eurogentec.com Kaneka Eurogentec Helpdesk
Catalaa Numbar	Tel. +32-4-3727665
Catalog Number Relevant identified uses of the substance/preparation and uses advised against	AS-65588 For laboratory use only.
Emergency information	Please contact the regional Eurogentec representation in your country or Kaneka Eurogentec S.A. directly (from 8 am to 6 pm)

Emergency Overview: We do recommend handling all chemicals with caution. Use proper protective equipment (PPE) when handling chemicals. To our knowledge, the hazards of this material have not been thoroughly investigated.

GHS Hazard Classification:

GHS Physical Hazards: Not a dangerous substance according to the GHS

GHS Health and Environmental Hazards: Not a dangerous substance according to the GHS

GHS Signal Words: None

GHS Hazard Statements: None

GHS Precautionary Statements: None

Potential Health Effects for:

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Good hygiene practice requires that exposure be kept to a minimum and that suitable control

measures be used in an occupational setting.

Ingestion: If swallowed, wash out mouth with water provided person is conscious. Call a physician.

Skin: In case of contact, immediately wash skin with soap and copious amount of water.

Eyes: In case of contact, immediately flush eyes with copious amounts of water for at least 15 minutes.

Chronic Exposures: No information available. We recommend limiting prolonged exposure.

Target Organs: No information available

HMIS Classification

Health hazard: 0

Chronic Health Hazard: 0

Flammability: 0
Physical hazards: 0

NFPA Rating

Health hazard: 0

Fire: 0

Reactivity Hazard: 0

3. Composition

Ingredients/Components:

Chemical Name: SHLP1 (Small humanin-like peptide 1)

H-MCH WAG GAS NTG DAR GDV FGK QAG-OH

Molecular formula: NA Molecular weight: 2393.6

CAS-No NA EC-No NA

4. First Aid Measures

Inhalation: If dust is inhaled, remove from contaminated area.

Encourage patient to blow nose to ensure clear passage of breathing.

If irritation or discomfort persists seek medical attention.

Ingestion:	If swallowed do NOT ind	
		atient forward or place on left side (head-down position, if possible) to
	maintain open airway and	prevent aspiration.
	Observe the patient carefu	ılly.
		buth, then provide liquid slowly and as much as casualty can comfortably
	drink.	
	Seek medical advice.	
Skin:	If skin or hair contact occ	urc.
Skiri.		unning water (and soap if available).
	Seek medical attention in	
<i>F</i>	If this product comes in co	
Eyes:		
	Wash out immediately wi	
		of the eye by keeping eyelids apart and away from eye and moving the
		ting the upper and lower lids.
	If pain persists or recurs s	eek medical attention.
5. Fire Fight	ting Measures	
Extinguishing media:		Water spray or fog.
		Alcohol resistant foam.
		Dry chemical powder.
		BCF (where regulations permit).
		Carbon dioxide
Special firefig	hting procedures:	Alert Emergency Responders and tell them location and nature of
		hazard.
		Wear breathing apparatus plus protective gloves.
		Prevent, by any means available, spillage from entering drains or water
		course.
		Use water delivered as a fine spray to control fire and cool adjacent
		area.
		DO NOT approach containers suspected to be hot.
		Cool fire exposed containers with water spray from a protected
		location.
		If safe to do so, remove containers from path of fire.
		Equipment should be thoroughly decontaminated after use.
Unusual fire d	and explosions hazards:	Emits toxic fumes under fire conditions
	ID I W	
v. Accidenta	l Release Measures	
Spill response		ignition sources.
		l spills immediately.
		act with skin and eyes.
		sonal contact by using protective equipment.
	Use dry cle	an up procedures and avoid generating dust.
	Place in a s	uitable, labeled container for waste disposal
Containment		ersonal contact, including inhalation.
		ctive clothing when risk of exposure occurs.
		ell-ventilated area.
		nter confined spaces until atmosphere has been checked.
		llow material to contact humans, exposed food or food utensils.
Ĭ.	Avoia cont	act with incompatible materials.

	When handling, DO NOT eat, drink or smoke.
	Keep containers securely sealed when not in use.
	Avoid physical damage to containers.
	Always wash hands with soap and water after handling.
	Use good occupational work practice.
	Empty containers may contain residual dust which has the potential to accumulate
	following settling. Such dusts may explode in the presence of an appropriate
	ignition source.
	Do NOT cut, drill, grind or weld such containers
	Do NOT cut, arm, grind of weld such containers
PPE	Use personal protective equipment
7 Handling and C4ar	
7. Handling and Stor	
Store at -20 °C desicca	ated and protected from light. Store away from oxidizing agent.
Ryposure Controls	: / Personal Protection
<u>-</u>	s / Personal Protection
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals;
_	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by
_	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
_	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace.
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur,
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge;
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type;
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks Build-up of electrostatic charge on the dust particle, may be prevented by bonding and
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks
<u>-</u>	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
8. Exposure Controls Engineering controls	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks Build-up of electrostatic charge on the dust particle, may be prevented by bonding and
_	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding. Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.
_	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding. Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting. Air contaminants generated in the workplace possess varying "escape" velocities which
_	Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and re-circulation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding. Powder handling equipment such as dust collectors, dryers and mills may require

9. Physical and Chemical Properties

Physical State	Solid
Odour	Not available
Solubility in Water	Not available
Specific Gravity	Not available
рН	Not available
Boiling Point	Not available
Melting Point	Not available
Flash Point	N/A
Vapor Pressure:	N/A
Vapor Density:	N/A

10. Stability and Reactivity

Thermal Decomposition	No data available
Dangerous Products of Decomposition	No data available

Toll-Free: 800-452-5530 • Tel: 510-791-9560 • Fax: 510-791-9573

Dangerous Reactions	COx, NOx when burned
Keen container tightly closed in a dry	well-ventilated place. Store in -20°C refrigerator

11. Toxicological Information

RTECS Number	N/A
Toxicity	No information available.
Health Hazards	Although ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.
Potential Hazards	Not available
Carcinogenicity:	No significant acute toxicological data identified
OSHA Permissible Exposure Limit(PEL) Data	N/A
ACGIH Threshold Limit Values (TLV)	N/A

Reproductive Toxicity: No information available

12. Ecological Information

No information available.

13. Disposal Considerations

All waste must be handled in accordance with local, state and federal regulations. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

14. Transport Information

Hazard Class	N/A
Identification Number	N/A
Packing Group	N/A
Proper Shipping Name (DOT)	N/A

15. Regulatory Information

California Proposition 65: N/A

US TSCA (Toxic Substance Control Act): N/A

US CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act: N/A

US SARA Title III (Superfund Amendments and Reauthorization Act: N/A

US Other: N/A

EC EINICS (European Inventory of Existing Commercial Chemical Substances) Number: N/A

EC Risk Statements: N/A

Other Country Regulations: N/A

16. Other Information

It is not intended for food, drug, household, agricultural or cosmetic use. A technically qualified individual experienced in handling potentially hazardous chemicals must supervise its use. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Users should make independent decisions regarding completeness of the information based on all sources available. AnaSpec shall not be held liable for any damage resulting from handling or from contact with the above product.